

You want power? You got it!



The American MUSCLE

FKD Series is designed for installation in circular ducts for applications where high airflows and quiet performance are needed: residential kitchen exhaust, supply/exhaust in institutional buildings such as offices, hospitals, beauty salons, veterinary clinics.

Airflow ranges between 675 and 5,800 cfm. Galvanized steel housing. Controllable with an external speed control between 20 and 100%.

FKD 8XL/KD 8XL 318W, 778 cfm 15 lbs	FKD 10/KD 10 305W, 848 cfm 14 lbs	FKD 10XL/KD 10XL 485W, 1203 cfm 21 lbs
--	--	---

FKD 12/KD 12 484W, 1245 cfm 20 lbs	FKD 12XL /KD 12XL 487W, 1865 cfm 38 lbs	FKD 14 491W, 2010 cfm 37 lbs
---	--	---

FKD 14XL 727W, 2470 cfm 45 lbs	FKD 16 727W, 2758 cfm 44 lbs	FKD 16XL 1609W, 4090 cfm 75 lbs
---	---	--

FKD 18 1637W, 4213 cfm 74 lbs	Wattage and airflow are given at 0.2 Pst.; 120V/1- See page 146 for full product specifications.	
--	---	--

FKD 8XL/KD 8XL 319W, 766 cfm 15 lbs	FKD 10/KD 10 299W, 815 cfm 18 lbs	FKD 14 491W, 1818 cfm 42 lbs
--	--	---

FKD 14XL 727W, 2183 cfm 51 lbs	FKD 16XL 1609W, 3558 cfm 75 lbs	FKD 18XL 2406W, 5220 cfm 98 lbs
---	--	--

FKD 20 2326W, 5345 cfm 99 lbs	Wattage and airflow are given at 0.2 Pst.; 230V/1- FKD 18XL and FKD 20XL 230-460V/3- See page 142 for full product specifications.	
--	--	--

Pair with these Accessories for KITCHEN EXHAUST 1200 cfm



**FKD 12XL/
KD 12XL**
Inline Fan

HL 42
Range Hood

RSK 12
Backdraft Damper

LD 12
Duct Silencer

RC 12P
Roof Cap



Industry leading EC products use up to 40% less electricity.

Our products provide controllability, high efficiency, long life span and low noise characteristics that are perfect for residential projects.

FKD EC Series offers same features as the muscle FKD fans along with built-in potentiometer to control the airflow between 0 and 100%. Ideal solution for projects where extra kick of exhaust air is needed on an irregular basis.



FKD 16 EC
1082W, 4010 cfm
109 lbs

FKD 16XL EC
1965W, 4016 cfm
112 lbs

FKD 18 EC
1979W, 5768 cfm
108 lbs

FKD 20 EC
2002W, 5840 cfm
109 lbs

Wattage and airflow are given at 0.2 Pst.
FKD16EC is a 230V/1-
FKD 16XL EC, FKD 18 EC and FKD 20 EC are 460V/3-
See page 143 for full product specifications.

FRESH AIR Intake?

Pair these accessories with an FKD:



AND



**FKD 8XL/
KD 8XL**
Inline Fan

ADC 8
Shut-off Damper



AND



AND



FGR 8
Filter Cassette

FML 8
Intake Air Vent

WC 15
Speed Control

